

# Supa range



## Sealing range

46-63	84-106	132-157	193-215	266-292	324-350	384-410
57-74	99-119	157-183	218-242	280-306	352-378	410-436
68-85	109-133	176-201	242-268	301-327	372-396	436-462

## Outside pipe diameter

Dn	Imp.Cast Iron Class AB/CD A/C (BS 486)	Steel Series 1, BS3600, API 5L BS1600, DIN 2460	UPVC BS3505, BS3506	Ductile Iron EN 545, BS 4772 ISO 2531, DIN 28600	Metric A/C Class 18/20	Metric A/C Class 25 ISO 160	Metric PVC DIN 8075, DIN 8074, ISO 360
40	55,9	48,3	48,3	56			50
50	69,1	60,3	60,3	66		69	63
60				77			
65	82,3	76,1	75,1	82	86		75
80	95,5	88,9	88,9	98	106	96	90
100	121,9	114,3	114,3	118	126	122	110
125	149,9	139,7/141,3	140,2	144	153		125/140
150	177,3	168,3	168,3	170	178	177	160
175	204,7	193,7	193,7				200
200	232,2	219,1	219,1	222	234/232	240	225
225	259,1	244,5	244,5		-/259	268	250
250	286	273	273	274	288/286	295	280
300	333,8/345,4	323,9	323,9	326	344/345	356	315
350	386,6/399,3	355,6	355,6	378	402/405	419	355
375	413/425,2						
400	439,4/453,1	406,4	406,4	429	456/463		400