



CONSTRUCTION

FOR LIFTING OF COMPLETE UNITS (EX LID)
 A 2 POINT EQUALISED SYSTEM USING THE
 1.3T SWIFTLIFT ONLY IS TO BE USED
 338 MESH, CENTRALLY PLACED.
 FINISHED PRODUCT WEIGHT 372kgs EXCLUDING THE LID

MATERIALS

CONCRETE STRENGTH (f_c) : 28 DAY STRENGTH SHALL BE 35mPa
 STRIPPING STRENGTH (min.) SHALL BE 15mPa
 REINFORCEMENT STEEL GRADE :IN ACCORDANCE WITH NZS3422 & NZS 3402
 HD BARS = GRADE 500E, MESH = 575mPa

MANUFACTURING STANDARDS

MANUFACTURE IN ACCORDANCE WITH NZS 3109:1997 (PRECAST UNITS)
 SURFACE FINISHED TO NZS3114:1987
 FORMED SURFACE - F4 FINISH
 TROWELLED SURFACES - U2 FINISH



Humes Pipeline Systems
 Private Bag 92817
 Auckland
 Freephone 0800 502 112
 www.humes.co.nz

Copyright: This design, information and drawing remain the property of Humes Pipeline Systems and may not be used or copied without approval in writing from Humes Pipeline Systems.

TELCO 600x600x600 HIGH
 ROADWAY CHAMBER
 (FIBRE OPTIC)

PLAN, ELEVATIONS, DETAILS & 3D DRAWING

Drawn By NW	Date 28/09/07
Checked By BR	Scale A1 AS SHOWN
Reference No. 04819	
Drawing No. SHEET 1	Rev. No. 1